	1	2	3	4		5			6			7		8
1			\ 0	- - - - 										
A	整机负载 Whole machine load	载重 Load	300Kg		¥*6	83	- a grand		_Ø9 贯	穿*6	\	O 2330	/8	
		电机型号 Motor	iSV2-CAN6020			and on the state of the state o	www.			1			0	
}		电机额定功率 Motor Rated Power	200W	000	/ >>\ \S\					18°		◎ ◎ -		
	电机参数	电机额定电压 Motor Rated Voltage	48V(DC)	_	Carried Anna	ano contraction of the contracti				١	Pol			
	Motor parameters	电机额定电流 Motor Rated Current	6A			arrayan man	······································				Ø100		1 Contract of the contract of	
		电机额定转速 Motor Rated Speed	3000 rpm											
		电机额定扭矩 Motor Rated Torque	0.64N*m											
		电机编码器类型 Servo Encoder	17位单圏磁编码器		-	324		-					0	
		行程 Route	60mm				7 1							
		丝杆规格 Screw rod specification	SFU2505	194.80		.			08					
七 号		减速机速比 Speed ratio of reducer	35			46.30			53.80				9	
件登记	升降参数 Lift parameter	传动齿比 Gear ratio	1			Ť			T					
3		升降速度 Up and down speed	6.94 mm/s											
<u></u>		升降时间 Up and down time	8.6s											
总号		限位传感器 Limit Sensor	常开NPN-24V Regular opening NPN-24V							-	IGK—SJ-	-300		300Kg顶升机构
总号	其他	齿盘润滑 lubrication	润滑脂 Grease			记 处数	分区 身		名 年月日	<u></u> 阶段		重量	比例	西安爱极客
字	Others	自重 Self weight	约16Kg		核	交核		标准化 工艺						"图样代号"
			<u> </u>		主管	设计	1	审核 批准		共1张	第1张	版本		 替代
	1	2	3	4		5	1	1,111,14	6	1 / 1 / 1	-1 17-	7		8